

Explosion Proof Armored Barrier Gland

The Explosion Proof Armored Barrier Gland is built for hazardous-area installations where cable entries must contain and isolate ignition risk. Available sizes, materials and packing options are listed in the parameter table. Send your application details and the sales team will verify the right specification before you order.

Product Information	
Product Name	Explosion Proof Armored Barrier Gland
Product family	Explosion-proof Cable Gland
Application	Waterproof electrical connection, cable entry or enclosure installation
RFQ note	Confirm model, thread or connector size, cable outside diameter, material request and quantity

Technical Parameters

Thread Size	Cable Range	Thread Length	Spanner Size	Outer Diameter
M12 x 1.5	3-6.5 mm	8 mm	14 mm	18 mm
M16 x 1.5	4-8 mm	8 mm	18 mm	22 mm
M20 x 1.5	6-12 mm	9 mm	22 mm	24 mm
M25 x 1.5	13-18 mm	10 mm	28 mm	33 mm
M32 x 1.5	18-25 mm	11 mm	36 mm	42 mm
M40 x 1.5	22-32 mm	12 mm	45 mm	52 mm
M50 x 1.5	32-38 mm	13 mm	55 mm	60 mm
M63 x 1.5	37-44 mm	14 mm	68 mm	75 mm

Values are for reference. Please confirm the exact specification with the sales team before ordering.